



Street Washing Machine
SL2V Model



High Pressure Street Washing

Technical Data

CHASSIS

articulated 4 wheels steel chassis

ENGINE

4 cylinder turbocharged diesel engine

VM type, 2776 cc displacement

maximum power 55 kW @ 2300 rpm

Step III homologated

CAB

steel structure

2 seats, right hand drive

TRANSMISSION

hydrostatic automotive type with electronic control

front drive

2 speed (travel-work)

SUSPENSIONS

sprung front axle with shock absorbers

rear axle with leaf springs & shock absorbers

STEERING

articulated, hydraulic assisted steering

BRAKES

4 wheels power assisted drum brakes

WASHING SYSTEM

water operated by 40 bar pump with delivery of 50 l./min.

Front wash jets with 6 nozzles + 4 side nozzles lhs/rhs mounted on adjustable bars

all controls in cabin

HOPPER

2000 litre water tank

stainless steel with internal breakwaters

PERFORMANCE

washing width max. 2800 mm

washing seep 12 km/h

travel speed 40 km/h

OPTIONS

air conditioning system

high pressure pump

spare wheel

rear view camera



Via S. Pellico, 2 - 20089 Rozzano (MI) - Italy - Tel. +39 02 57514340 - Fax +39 02 57513878

Sicas Euroclean Industrial

www.sicaseuroclean.eu