

STREET WASHING MACHINE SL5000 MODEL



Millennium New Generation Euro 5 EEV

TECHNICAL DATA

CHASSIS

4 wheel, steel chassis, automotive design

MOTOR

4 cylinder common rail diesel engine

MAN 4580 cc model D0834LFL61

rated output 132 kW @ 2400 rpm

Euro 5 EEV homologated

CABIN

steel structure

2 seats, drivers station can glide from left to right

TRANSMISSION

hydrostatic, automotive type with electronic control

rear drive

2 speed mode (travel - work)

SUSPENSION

front: floating axle with rubber coated springs and shock absorbers

rear: leaf springs

STEERING

hydraulic system

BRAKES

4 wheel disc brakes with dual calipers on all wheels

WASHING SYSTEM

water operated by 3 cylinder pump from 40 to 100 bar delivery from 60 to 133 l/min.

front wash jets with 10 adjustable nozzles

all controls in cabin

HOPPER

5500 litre water tank

AISI 304L stainless steel tank

PERFORMANCE

standard washing width 1800 mm

washing speed 15 km/h.

travel speed 42 km/h

MAIN OPTIONS

air conditioning

high pressure pump

wash jet lance with automatic front reel

spare wheel

rear view camera

telescopic top fitting

